

NFC Multi Pad



SPAY-2900

The versatile yet extremely compact SPAY-2900 is fashionably presented by SCSpro. It would be your cost-effective choice in today's competitive market, while maintaining just as much contactless capabilities and usability for multi-applications.

With Serial ports SPAY-2900 supports simultaneous communications with two other POS or CAT terminals, bridging data and information sharing in real-time.

SCSpro Co., Ltd

SmartCard Solution Professional



Hardware Specification

Model		SPAY-2900
Type		NFC Multi Pad (with Signature & PIN-Pad Functions)
Processor		Cortex-M3 100Mhz
O/S		RTOS
Memory	Flash	512KB
	SRAM	64KB
Display	LCD	2.9" FSTN White 128 x 64 Pixels
	LED	RF Indicators*4 (Blue, Yellow, Green, Red)
Touch Type		4-Wire Analog Resistive Touch Panel
Cards	Contact	N/A
	Contactless	ISO14443 Type A/B, Mifare, FeliCa, ISO18092 (NFC)
	SAM	Max. Slots*4
Sound		Buzzer
RTC		Yes
External Interface	USB	Device*1
	Serial	RS-232 RJ11 Port*2
	Ethernet	N/A
	WiFi	N/A
	CDMA/GSM/GPRS	N/A
	SD Card	N/A
Features		Simultaneous connections to 2 POS / CAT terminals
Operating Temp.		0°C ~ 50°C
Dimensions		99.5mm (L) x 112mm (W) x 26.5mm (H)
Power Adaptor		Input: AC100V~240V 0.3A 50-60Hz, Output: DC+5V ±5%, 2A
Certifications		 

