



# IDBridge CT30 smart card reader

## Universal reader for smart card applications

### Protecting Executives

Cyber attack and identity theft continue to increase and become more sophisticated as businesses harness the power of online services for business applications. To counteract this threat, many enterprises, financial institutions and government agencies have deployed strong authentication using smart card technology to provide safe logical access, protect digital identities and secure online transactions of their employees, customers and citizens at large.

#### The IDBridge CT30 benefits:

- > Data and identity protection
- > Strong authentication
- > Secure application for eGov, enterprise, healthcare, banking, gaming
- > Easy to deploy
- > Universal for all ISO smart cards
- > Customizable



# IDBridge CT30 smart card reader

Smart card readers are an essential component of any smart card deployment. Connected to a PC, laptop or thin client, they ensure communication between the smart card and network services, and must do so in a convenient yet secure manner. Gemalto's full range of PC-Link smart card readers provide the perfect balance of ease of use combined with the highest level of security.

## Main standard compliances

- > ISO7816
- > EMV2000 Level 1
- > Microsoft signature (WHQL)
- > USB 2.0 and CCID 1.1
- > RoHS and REACH
- > PC/SC

The innovative transparent design of the IDBridge CT30 highlights the card with your graphics. A flexible deployment solution with maximum user-friendliness, the IDBridge CT30 is compact and lightweight to optimize shipping expenses and offers a cost effective solution to all your smart card reader needs.

The IDBridge CT30 is modular in concept, and several easy-to-use and easy-to-install accessories are available, including a stand for desktop use (vertical insertion) and floppy disk tray to convert the reader to an internal device to be installed in a PC Floppy Disk or CD-ROM bay.

TECHNICAL SPECIFICATIONS		
<b>Host interface</b>		<ul style="list-style-type: none"> <li>• USB 2.0, full speed (12Mbps/s), hubless, CCID protocol</li> </ul>
<b>Operating systems, drivers and API</b>		<ul style="list-style-type: none"> <li>• Windows : up to Windows 8 (Microsoft signature)</li> <li>• Linux</li> <li>• Mac OS</li> <li>• CT-API</li> <li>• Synchronous API for memory cards</li> </ul>
<b>Standards</b>		<ul style="list-style-type: none"> <li>• ISO7816-1, 2, 3, 4</li> <li>• EMV terminal level 1 version 4</li> </ul>
<b>Supported smart cards</b>	Asynchronous	<ul style="list-style-type: none"> <li>• Microprocessor cards</li> <li>• T=0, T=1 protocols</li> <li>• Transmission rate: 2 Kbps to 826Kbps (TA1=17 @ CK=4.8MHz)</li> </ul>
	Synchronous	<ul style="list-style-type: none"> <li>• Through the Command Interpreter</li> </ul>
<b>Smart card electrical interface</b>	Smart card power supply	<ul style="list-style-type: none"> <li>• 5V and 3V and 1.8V</li> <li>• Short circuit current limitation</li> <li>• Power up / power down control sequences</li> </ul>
	Smart card management	<ul style="list-style-type: none"> <li>• Card insertion/extraction detection</li> </ul>
	ESD protection on card I/O	<ul style="list-style-type: none"> <li>• 8KV Human Body Model</li> </ul>
	Power down	<ul style="list-style-type: none"> <li>• Less than 200µA suspend mode current</li> </ul>
<b>Human interface</b>	Led	<ul style="list-style-type: none"> <li>• Green led with dual state (waiting and operation)</li> </ul>
<b>Temperature</b>		<ul style="list-style-type: none"> <li>• Operating range: 0°C to +55°C</li> <li>• Storage: 0°C to +70°C</li> </ul>
<b>Environmental</b>		<ul style="list-style-type: none"> <li>• RoHS, REACH</li> <li>• WEEE</li> <li>• CE, FCC part 15, VCCI, c-Tick, BSMI, KC</li> <li>• EN60950 / UL-cUL60950</li> </ul>
<b>Dimensions</b>	Reader	<ul style="list-style-type: none"> <li>• 74mm x 63mm x13mm</li> <li>• Weight 55g</li> </ul>
	Cable	<ul style="list-style-type: none"> <li>• 1.5m (59.1") USB2.0 with type A connector</li> </ul>
	Carton box	<ul style="list-style-type: none"> <li>• 108mm x 90mm x 30mm</li> </ul>
<b>Other features</b>	Color	<ul style="list-style-type: none"> <li>• Transparent (crystal)</li> </ul>